

# DATA SHEET

## Titan XQ 600 puls DW

090-005563-00001



- MIG/MAG inverter welding machine, pulse, with separate wire feeder
- Perfect MIG/MAG weld seams even with long welding leads
- Synergic control with one-knob operation
- No controls on the welding machine.
- The machine is controlled exclusively via the selected wire feeder.


**all in**

**No need to purchase additional characteristics – all characteristics for this machine type are included in the scope of delivery ex works**

- With innovative EWM Synergic characteristics rootArc<sup>®</sup> XQ/rootArc<sup>®</sup> puls XQ, coldArc<sup>®</sup> XQ/coldArc<sup>®</sup> puls XQ, forceArc<sup>®</sup> XQ/forceArc<sup>®</sup> puls XQ, wiredArc XQ/wiredArc puls XQ, pulse/superPuls and Positionweld
- With Synergic characteristics for GMAW standard or pulsed welding for steel/CrNi/aluminium
- Non Synergic operation for manual setting of welding parameters
- Suitable for MMA welding, TIG welding and gouging
- Individually configurable programmes for each welding task (JOB)
- Adjustable start and end-crater functions
- Infinitely adjustable arc dynamics (choke effect)
- **Your benefits**
- flexFit casing system: Many accessory parts and options can be fixed to the welding machine using conventional slot nuts
- LED information bar: Indicates the current operating status
- Drive XQ / Drive XQ IC 200 with high-precision, powerful EWM eFeed 4-roll drive to reliably feed all solid and flux cored wires
- Energy-saving thanks to high efficiency and standby function
- Best suited for use with long hose packages
- Connection capability for remote control and function torch
- Easy, tool-free change of welding polarity
- Insulated wire space
- IP23 spray water protected
- Optional network connectivity with the ewm Xnet software via an integrated or external gateway
- PC interface for PC300 XQ software
- The high 1500 W cooling capacity, high-performance centrifugal pump and 8-litre coolant tank make for excellent torch cooling, resulting in cost savings on consumables
- Free WPQR package for certification up to and including EXC2 in accordance with EN 1090 and for welding of unalloyed steels up to and including S355

# DATA SHEET

## Titan XQ 600 puls DW

Version	Titan XQ 600 puls D W R1 5m
Setting range for welding current	5 A - 600 A
Duty cycle 40 °C	600 A / 40 % 550 A / 60 % 470 A / 100 %
Open circuit voltage	82 V
Mains voltage	3 x 400 V
Tolerances	-25 % up to +20 %
Mains frequency	50 Hz / 60 Hz
Recommended generator power	46 kVA
Wire feed speed	0.5 m/min - 25 m/min 19.685 ipm - 984.253 ipm
Cooling capacity at 1 l/min.	1500 W
Pump pressure	3.5 bar
Tank capacity	8 l
Protection classification	IP23
Test mark	
EMC class	A
Dimensions (L x B x H)	1150 mm x 678 mm x 972 mm 45.3 inch x 26.7 inch x 38.3 inch
Weight	128.5 kg / 283.3 lbs
Standards	IEC 60974-1, -2 and -10 CL.A

### Configurations

Item no.	Designation
090-005563-00000	Titan XQ 600 puls D. Multiprocess MIG/MAG pulse welding machine including all characteristics and welding processes,
092-003303-00000	OW F06W. Water cooling
092-003306-00000	OW Cover. No control
092-003316-00000	OW F06R1. Wheel kit with single cylinder mount
092-003349-00000	OW MCord 6 mm <sup>2</sup> 5m. Mains connection lead, 5 m