



# MIG CLEARO2 W200

## INTEGRATED FUME EXTRACTION

FOR TWO WELDER



**CLEARO2  
UNITS**



<b>Dimensions</b>	(L x B x H) 700 x 530 x 560 / 630mm (without / with wheels)
<b>Implementation</b>	Mobile on 4-wheels. Two rotating with locks
<b>Power Supply</b>	400 - 480 V / 50 - 60 Hz
<b>Motor power</b>	Max 3.0 KW
<b>Suction Flow</b>	Max. 250 m³/h (free blowing)
<b>Suction Flow Effective</b>	Max. 65m³/h
<b>Working Pressure</b>	Max. 45000Pa (el. Controlled)
<b>Filter Surface</b>	5m² Active filter surface, Filter efficiency: IFA >99.8%
<b>Working Temperature</b>	0 to +50°C
<b>Max. DC</b>	DC: 100%
<b>Inlet</b>	51 mm
<b>Weight</b>	Ca. 58 kg
<b>Noise Level</b>	Max. dB(A) <65Db(A) (at 100% suction flow)
<b>Filter method</b>	Disposable filter
<b>Certifications</b>	CE, W3, and CSA

**EXTRACTION**

PART NO.	DESCRIPTION	PACK QTY
<b>CLEARO2 W200</b>		
3746200000000	Welding fume unit ClearO2 W200 380 - 420 V 50 - 60 Hz 3 KW	1